

Acetylene Black Granular -03

Description

Acetylene Black in granular form provides an alternative to compressed powder that allows for easy handling and dust reduction. Granular product has superior purity, absorption, and conductivity. This product can be used in a variety of applications such as tire bladders, rubber, cable coatings, plastics and batteries.

Properties

| Properties | AB Granular |
|---|-------------|
| Oil Absorption Value ml/100g | 180 - 220 |
| Iodine Absorption mg/g | 80 - 110 |
| Bulk Density g/l | 210 - 260 |
| PH Value | 6 - 9.5 |
| Moisture (wt%) | ≤ 0.20 |
| Fines (wt%) | < 6 |
| Ash Content (wt%) | ≤ 0.20 |
| Grit 325 mesh (ppm) | < 30 |
| Individual Pellet Crushing Strength (g) | < 5 |

Packaging

Available in 22 lb. paperbags or polybags and 661 lb. super sacks

No warranties, express or implied, including warranties of merchantability or fitness for a particular use are made with respect to the products described herein. Nothing contained herein shall constitute permission or a recommendation or inducement to practice any invention covered by a patent without the permission of the patent owner. Customers/users are advised to test the product in advance to make certain it is suitable for their particular production conditions and use or uses of the product. Seller shall not be liable for and the customer assumes all risk and liability for any use or handling of the product.