

## Alkylate Fluids

### Description

Branched and linear alkylbenzene (BAB) is produced by reacting benzene with various propylene oligomers to produce different molecular weights. Linear alkylbenzene (LAB) is produced by reacting benzene with linear alpha olefins producing a range of different molecular weight products. Alkylates provide superior low temperature properties, excellent oxidative and thermal stability, compatible with elastomers, seal swell and improved solubility.

End uses: raw materials for surfactants and synthetic sulfonates, base oil for specialty lubricants and functional fluids. Used in agriculture and electronic components and equipment.

### Properties

SPECIFICATION	ASTM	A 6	A 14	A 32	A 46	A 68	A 100
Color, Max	D1500	1.0	1.0	1.5	1.5	1.5	1.5
Kinematic Viscosity (cSt) @ 40 °C	D445	4.0 - 7.0	18 - 28	29 - 35	42 - 50	50 - 70	85 - 105
Flash Point (COC), °C, min	D92	125	185	170	170	170	170
Water, ppm, max	D1533	100	100	100	100	100	100
<b>TYPICAL PROPERTIES</b>							
Specific Gravity	D1298	0.86	0.86	0.86	0.865	0.875	0.88
Pour Point , °C, max	D97	-40	-40	-40	-35	-30	-30
Floc Point , °C, max	ASH-86	-65	-65	-65	-60	-55	-55
Acid Number, mg KOH/g, max	D974	0.02	0.02	0.02	0.02	0.02	0.02
Average Molecular Weight	D3593	239	324	324	324	350	500

### Packaging

Product available in bulk tank trucks, iso-containers, totes & drums

No warranties, express or implied, including warranties of merchantability or fitness for a particular use are made with respect to the products described herein. Nothing contained herein shall constitute permission or a recommendation or inducement to practice any invention covered by a patent without the permission of the patent owner. Customers/users are advised to test the product in advance to make certain it is suitable for their particular production conditions and use or uses of the product. Seller shall not be liable for and the customer assumes all risk and liability for any use or handling of the product.