

TECHNICAL DATA SHEET

June 2018

TIMREX[®] C-LUB304 **TIMCAL Graphite**

Carbon Lubricant

Synthetic Graphite-Containing

General Characteristics

Formula: Carbon Aspect: Fine black powder

Standard Packaging 15 kg paper bags, 39 bags on one pallet (585 kg)

Guaranteed Values

Ash	0.5	% max
Moisture	0.5	% max
D90 (Laser Diffraction)	7.2-11.2	μm

Typical Values

Purity		
Ash	0.2	%
Moisture	0.1	%
Density		_
Scott	0.09	g/cm ³
Particle Size Distribution		
Laser Diffraction		
D10	1.9	μm
D50	4.9	μm
D90	9.9	μm
		•

Imerys Graphite & Carbon Switzerland Ltd. Strada Industriale 12 - 6743 - Bodio - Switzerland Tel: +41 91 873 20 10 - Fax: +41 91 873 20 19 - www.imerys-graphite-and-carbon.com

Imerys Graphite & Carbon is a trademark of the Imerys Group

The information contained herein is believed to be correct. However, no warranty is made, either expressed or implied regarding the accuracy or the results to be obtained

The information contained instantial below to be construct noticed in the matching instantial structure of such information. The user assumes all risk and liability for intellectual property infringement and no statement(s) made in relation to this material is intended or shall be construed as inducing infringement of a valid patent.