

SECTION 1: IDENTIFICATION

Product Identifier

Product Form: Mixture

Product Name: Thixocal 5752A

Product Code: Thixocal 5752A

Intended Use of the Product

Use of the Substance/Mixture: Corrosion Preventive Compound.

Name, Address, and Telephone of the Responsible Party

Company

Soltex Inc. (Synthetic Oils & Lubricants of Texas)

4 Waterway Square Place, Suite 275

The Woodlands, TX 77380

(281)-587-0900

soltexinc.com

Emergency Telephone Number

Emergency Number : (800)-424-9300 (CHEMTREC); (281)-587-0900 (Other Safety Information)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the chemical in accordance with paragraph (d) of §1910.1200:

**GHS
Hazard
Symbols:**



GHS Classification:

Flammable Liquid Category 3; Specific Target Organ Systemic Toxicity (STOT)
- Single Exposure Category 3

Signal Word:

Warning

Hazard Statements:

Flammable liquid and vapor
May cause respiratory irritation

Unclassified Hazards (HNOC):

None Identified

Precautionary Statements:

Prevention:

Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Avoid breathing fume/gas/mist/ vapors/spray.
Use only outdoors or in a well-ventilated area.

Response:

Wear protective gloves/protective clothing/eye protection/face protection.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
If inhaled: Remove person to fresh air and keep comfortable for breathing.
Call a poison center/doctor if you feel unwell.
In case of fire: Use appropriate media to extinguish.

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Storage: Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool.
Store locked up.

Disposal: Dispose of contents/container to a suitable disposal site in accordance with local/national/international regulations.

Hazards not otherwise classified: No data available

o-#u@V' #\ U h\ o@V @\ kU ° u@V \ V @8k-) @Vuo'

Mixtures

Chemical name	Common name and synonyms	CAS No.	%
Distillates (petroleum), hydrotreated light	None	64742-47-8	45 - 70

Note: Specific chemical identities and/or exact percentages have been withheld as a trade secret.

o-#u@V' 7@cu" @ U - ° oyk-o'

Description of necessary measures, subdivided according to the different routes of exposure, i.e., inhalation, skin and eye contact, and ingestion:

Inhalation: If symptoms are experienced remove source of contamination or move victim to fresh air and obtain medical advice.

Eye Contact: Flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention.

Skin Contact: Wash with soap and water. Get medical attention if irritation develops or persists.

Ingestion: Do not induce vomiting and seek medical attention immediately. Provide medical care provider with this SDS.

Most important symptoms/effects, acute and delayed: May cause respiratory irritation

Indication of immediate medical attention and special treatment needed, if necessary: Consult a physician. Treat symptomatically.

o-#u@V' 7@- 7@=u@8U - ° oyk-o'

Suitable (and unsuitable) extinguishing media:

Suitable extinguishing media: Use alcohol resistant foam, carbon dioxide, dry chemical, or water spray when fighting fires. Water or foam may cause frothing if liquid is burning but it still may be a useful extinguishing agent if carefully applied to the fire.

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical: Vapors may be ignited by sparks, flames or other sources of ignition if material is above the flash point giving rise to a fire (Class B). Vapors are heavier than air and may travel to a source of ignition and flash back. Empty containers that retain product residue (liquid, solid/sludge, or vapor) can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose container to heat, flame, sparks, static electricity, or other sources of ignition. Any of these actions can potentially cause an explosion that may lead to injury or death.

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Hazardous combustion products:

Carbon dioxide, Carbon monoxide, Hydrocarbons, Sulfur oxides

Special protective equipment and precautions for fire-fighters:

Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products. Use appropriate methods for the surrounding fire.

o-#u@V ° ##@-Vu° Ok-Q° o-U-° oyk-o°

Personal precautions, protective equipment and emergency procedures:

No health effects expected from the clean-up of this material if contact can be avoided. Follow personal protective equipment recommendations found in Section VIII of this SDS

Methods and materials for containment and cleaning up:

Absorb or cover with dry earth, sand or other non-combustible material and transfer to appropriate waste containers. Use clean, non-sparking tools to collect absorbed material. Collect and discard in accordance with local, state and national regulations.

o-#u@V ° =° V) @/8° V) o\k° 8-

Precautions for safe handling:

Mildly irritating material. Avoid unnecessary exposure. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. Do not get in eyes, on skin and clothing. Wash thoroughly after handling. As with all chemicals, good industrial hygiene practices should be followed when handling this material. Prevent small spills and leakage to avoid slip hazard.

Conditions for safe storage, including any incompatibilities:

Safe storage conditions:

Store in a cool dry place. Isolate from incompatible materials. Keep away from heat, sparks, and flame. Keep container closed when not in use.

Materials to Avoid/Chemical Incompatibility:

Strong oxidizing agents

o-#u@V ° -CE\oyk- #\ Vuk\ @ h-ko\ V° Ohk\ u-#u@V°

OSHA permissible exposure limit (PEL), American Conference of Governmental Industrial Hygienists (ACGIH) Threshold Limit Value (TLV), and any other exposure limit used or recommended by the chemical manufacturer, importer, or employer preparing the safety data sheet, where available:

Chemical component	OSHA PEL	ACGIH TLV	ACGIH STEL	IDLH
Distillates (petroleum), hydrotreated light		200 mg/m3		No data available

Appropriate engineering controls:

Local exhaust ventilation or other engineering controls are normally required when handling or using this product to avoid overexposure.

Engineering controls must be designed to meet the OSHA chemical specific standard in 29 CFR 1910.

Individual protection measures, such as personal protective equipment:

Respiratory Protection:

Proper ventilation (at a minimum) will be required when handling this product. Use respirators (NIOSH approved) only if ventilation cannot be used to eliminate symptoms or reduce the exposure to below acceptable levels.

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Respirator Type(s):	NIOSH approved air purifying respirator with organic vapor cartridge.
Eye protection:	Wear chemically resistant safety glasses with side shields when handling this product. Do not wear contact lenses. When handling material that is heated, wear chemically resistant safety glasses with side shields and a face shield.
Skin protection:	Wear protective gloves. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work.
Gloves:	When handling material that is heated, wear thermally protective heat insulating chemically resistance gloves. If contact with forearms is likely, wear gauntlet style gloves., Chemically resistant gloves.
Other protective equipment:	Wear chemically resistant safety glasses with side shields when handling this product. Do not wear contact lenses. Wear protective gloves. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work. When handling material that is heated, wear chemically resistant safety glasses with side shields and a face shield.
General hygiene conditions:	Use with adequate ventilation Do not use pressure to empty container. Remove contaminated clothing and wash before reuse. Avoid contact with material, avoid breathing dusts or fumes, use only in a well-ventilated area. Ground and bond containers when transferring material. Use spark-proof tools and explosion-proof equipment. Prevent small spills and leakage to avoid slip hazard. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. Do not get in eyes, on skin and clothing. Wash thoroughly after handling. As with all chemicals, good industrial hygiene practices should be followed when handling this material.

o- #u@V ' h=' o@° O° V) #-U @° Ohk\ h-ku@o

Appearance (physical state, color etc.):	
Physical state:	Viscous Liquid
Color:	Off-white
Odor:	Hydrocarbon Solvent Slight
Odor Threshold:	No data available
pH:	No data available
Melting point/freezing point (°C):	No data available
Melting Point (°C):	No data available
Freezing point (°C):	No data available
Initial boiling point and boiling range (°C):	No data available
Flash Point:	>= 105 °F (41 °C)
Evaporation Rate:	<1 (n-Butyl Acetate=1)
Flammability (solid, gas):	No data available

Upper/lower flammability or explosive limits:

Upper flammability or explosive limits:	No data available
Lower flammability or explosive limits:	No data available
Vapor pressure:	3.4 mmHg @ 20°C
Vapor density:	>1 (Air=1)
Relative density:	0.884
Solubility(ies):	Negligible; 0-1%
Partition coefficient: n-octanol/water:	No data available
Auto-ignition temperature (°C):	No data available
Decomposition Temperature (°C):	No data available
Viscosity:	4600 cP
Volatiles, % by weight:	45.7
VOC, Material, lb/gal	3.35
VOC, Material, grams/liter	401
VOC minus exempt solvents & water, g/L	403

SECTION 10: STABILITY AND REACTIVITY

Reactivity:	Not expected to be reactive
Chemical stability:	Hazardous polymerization will not occur.
Possibility of hazardous reactions:	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid (e.g., static discharge, shock, or vibration):	Temperatures above flash point in combination with sparks, open flames, or other sources of ignition. Elevated temperatures. Contamination.
Incompatible materials:	Strong oxidizing agents
Hazardous decomposition products:	Under normal conditions of use & storage, decomposition and hazardous decomposition products are unlikely.

SECTION 11: TOXICOLOGICAL INFORMATION

Description of the various toxicological (health) effects and the available data used to identify those effects:

Information on the likely routes of exposure (inhalation, ingestion, skin and eye contact): Eye contact, Skin contact, Inhalation

Symptoms related to the physical, chemical and toxicological characteristics: May cause respiratory irritation

Delayed and immediate effects and also chronic effects from short- and long-term exposure:

Ingestion Toxicity:	Harmful if swallowed. Estimated to be > 5.0 g/kg; practically non-toxic.
Skin Contact:	Can cause minor skin irritation, defatting, and dermatitis.
Inhalation Toxicity:	May cause respiratory irritation
Eye Contact:	Can cause moderate irritation, tearing and reddening, but not likely to permanently injure eye tissue.
Sensitization:	None known
Mutagenicity:	No data
Reproductive and Developmental Toxicity:	No data available.

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Carcinogenicity: There are no carcinogenic ingredients present at or over 0.1%.
STOT-single exposure: Classification has been based on toxicological information of the components in Section 3.
STOT-repeated exposure: Based on available data, the classification criteria are not met.
Aspiration hazard: Based on available data, the classification criteria are not met.

Numerical measures of toxicity (such as acute toxicity estimates):

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Distillates (petroleum), hydrotreated light			Inhalation LC50 (4h) Rat > 20 mg/L

Is the hazardous chemical listed in the National Toxicology Program (NTP) Report on Carcinogens (latest edition) or has it been found to be a potential carcinogen in the International Agency for Research on Cancer (IARC) Monographs (latest edition), or by OSHA?:

Chemical Name	OSHA Carcinogen	IARC Carcinogen	NTP Carcinogen
No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen.			

SECTION 12: ECOLOGICAL INFORMATION

Ecological Toxicity Data:

Chemical Name	CAS #	Aquatic EC50 Crustacea	Aquatic ERC50 Algae	Aquatic LC50 Fish
No data available				

Persistence and degradability: No data
Bioaccumulative potential: No data available
Mobility in soil: No data available
Other adverse effects (such as hazardous to the ozone layer): No data available

SECTION 13: DISPOSAL CONSIDERATIONS

Description of waste residues and information on their safe handling and methods of disposal, including the disposal of any contaminated packaging: Spent or discarded material may be a hazardous waste. Dispose of in accordance with Local and National regulations.

Waste codes / waste designations: D001

SECTION 14: TRANSPORT INFORMATION

Domestic Ground in containers <= 119 GL	Corrosion preventive/Non-Regulated
Domestic Ground in containers > 119 GL	UN1268, PETROLEUM DISTILLATES, N.O.S., (Naphtha Solvent), Combustible liquid, PG III
Shipping name for Export, Air (IATA)	UN1268, PETROLEUM DISTILLATES, N.O.S., (Naphtha Solvent), 3, PG III
Shipping name for Export, Sea (IMDG)	UN1268, PETROLEUM DISTILLATES, N.O.S., (Naphtha Solvent), 3, PG III
Marine Pollutant?	No

SECTION 15: REGULATORY INFORMATION
International Inventory

Country(s) or region		On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippines Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Inventory	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or are unknown from listing on the inventory administered by the governing country(s).

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

<u>Chemical Name</u>	<u>CAS #</u>	<u>Regulation</u>	<u>Percent</u>
Naphthalene	91-20-3	Prop. 65 - Cancer	TRACE
Cumene	98-82-8	Prop. 65 - Cancer	TRACE
Benzene	71-43-2	Prop. 65 - Cancer	TRACE
Ethylbenzene	100-41-4	Prop. 65 - Cancer	TRACE
Benzene	71-43-2	Prop. 65 - Developmental and/or Reproductive	TRACE
Toluene	108-88-3	Prop. 65 - Developmental and/or Reproductive	TRACE
Toluene	108-88-3	CERCLA	TRACE RQ = 1000 lbs
Naphthalene	91-20-3	CERCLA	TRACE RQ = 100 lbs.
Cumene	98-82-8	CERCLA	TRACE RQ = 5000 lbs.
Benzene	71-43-2	CERCLA	TRACE RQ = 10 lbs.
Ethylbenzene	100-41-4	CERCLA	TRACE RQ = 1000 lbs.
Naphthalene	91-20-3	SARA 313	TRACE
Cumene	98-82-8	SARA 313	TRACE
Benzene	71-43-2	SARA 313	TRACE
Ethylbenzene	100-41-4	SARA 313	TRACE
Toluene	108-88-3	SARA 313	TRACE
No SARA 302 EHS-listed chemicals in this product.		SARA EHS	

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision Date : 03/05/2026
Version # : 1.2
Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

Party Responsible for the Preparation of This Document

Synthetic Oils and Lubricants of Texas
 4 Waterway Square Place, Suite 275
 The Woodlands, TX 77380
 281-587-0900
www.soltexinc.com

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.