



Soltex Inhibsol 10

Description

Soltex Inhibsol 10 is genuine, unused, naphthenic transformer oil blended with 2,6-di-ter-butyl-pcresol (BHT) to a concentration of 10% by mass. Inhibsol 10 is conveniently packaged and ready to use for maintenance and service personnel looking to accurately raise oxidation inhibitor levels in the oil of in-service transformers and other oil-filled equipment.

Typical Properties

| Typical Properties | Units | Test Method | Specification | Typical |
|--------------------------------------|--------|-------------|----------------|---------|
| Antioxidant, Phenols | wt% | Calculate | 9.5 - 10.5 | 10.0 |
| Dielectric dissipation factor @ 90°C | | ASTM D 924 | 0.005 max | 0.001 |
| Density @ 15°C | lb/gal | ASTM D 1475 | Report | 7.44 |
| Specific Gravity @ 15.0°C | | ASTM D 1298 | Report | 0.89 |
| Appearance | | | Clear & Bright | C & B |

Packaging

Bulk tank trucks, iso-containers, totes, drums & pails

No warranties, express or implied, including warranties of merchantability or fitness for a particular use are made with respect to the products described herein. Nothing contained herein shall constitute permission or a recommendation or inducement to practice any invention covered by a patent without the permission of the patent owner. Customers/users are advised to test the product in advance to make certain it is suitable for their particular production conditions and use or uses of the product. Seller shall not be liable for and the customer assumes all risk and liability for any use or handling of the product.