

SECTION 1: IDENTIFICATION

Product Identifier: 1797

Product Form: Mixture

Product Name: Thixocal 5000A

Product Code: Thixocal 5000A

Intended Use of the Product

Use of the Substance/Mixture: Corrosion Preventive Compound.

Name, Address, and Telephone of the Responsible Party

Company

Soltex Inc. (Synthetic Oils & Lubricants of Texas)

3707 FM 1960 W Ste. 560

Houston, TX 77068

(281)-587-0900

soltexinc.com

Emergency Telephone Number

Emergency Number : (800)-424-9300 (CHEMTREC); (281)-587-0900 (Other Safety Information)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the chemical in accordance with paragraph (d) of §1910.1200;

**GHS Hazard
Symbols**



GHS Classification

Skin Corrosion/Irritation Category 2.

Flammable Liquid Category 3.

Specific Target Organ Systemic Toxicity (STOT) - Single Exposure Category 3.

Signal Word

Warning.

Hazard Statements

Flammable liquid and vapour.

Causes skin irritation .

May cause drowsiness or dizziness.

**Unclassified
Hazards (HNOC)**

None identified

**Precautionary Statements
Prevention**

Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/ vapors/spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

Response

If on skin: Wash with plenty of water.

If on skin (or hair): Take off immediately all contaminated clothing.

Rinse skin with water/shower.

If inhaled: Remove person to fresh air and keep comfortable for breathing.

Thixocal 5000A

Safety Data Sheet

Call a poison center/doctor if you feel unwell.
Specific treatment: see Section 4 on this SDS.
If skin irritation occurs: Get medical advice/attention.
Take off contaminated clothing and wash it before reuse.
In case of fire: Use appropriate media to extinguish.

Storage

Store in a well-ventilated place.
Keep container tightly closed.
Keep cool.
Store locked up.

Disposal

Dispose of contents/container to a suitable disposal site in accordance with local/national/international regulations.

Hazards not otherwise classified

No data available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	Common name and synonyms	CAS #	%
Hydrotreated light distillate (Petroleum)	None	64742-47-8	30 - 60

Note: Specific chemical identities and/or exact percentages have been withheld as a trade secret.

SECTION 4: FIRST AID MEASURES

Description of necessary measures, subdivided according to the different routes of exposure, i.e., inhalation, skin and eye contact, and ingestion:

Inhalation	If symptoms are experienced remove source of contamination or move victim to fresh air and obtain medical advice.
Eyes	Flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention.
Skin Contact	Wash with soap and water. Get medical attention if irritation develops or persists.
Ingestion	Do not induce vomiting and seek medical attention immediately. Provide medical care provider with this SDS. If vomiting occurs, lean victim forward to reduce risk of aspiration into lungs.

Most important symptoms/effects, acute and delayed Causes skin irritation. May cause drowsiness or dizziness.

Indication of immediate medical attention and special treatment needed, if necessary Consult a physician. Treat symptomatically.

SECTION 5: FIRE-FIGHTING MEASURES

Suitable (and unsuitable) extinguishing media:

Suitable extinguishing media	Use alcohol resistant foam, carbon dioxide, dry chemical, or water spray when fighting fires. Water or foam may cause frothing if liquid is burning but it still may be a useful extinguishing agent if carefully applied to the fire.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical: Vapors may be ignited by sparks, flames or other sources of ignition if material is above the flash point giving rise to a fire (Class B). Vapors are heavier than air and may travel to a source of ignition and flash back. Empty containers that retain product residue (liquid, solid/sludge, or vapor) can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose container to heat, flame, sparks, static electricity, or other sources of ignition. Any of these actions can potentially cause an explosion that may lead to injury or death.

Thixocal 5000A

Safety Data Sheet

Hazardous combustion products

Oxides of carbon, Formaldehyde, Hydrocarbons, Calcium oxides, Sulfur oxides.

Special protective equipment and precautions for fire-fighters

Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products. Use appropriate methods for the surrounding fire.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

No health effects expected from the clean-up of this material, if contact can be avoided. Follow personal protective equipment recommendations found in Section VIII of this SDS.

Methods and materials for containment and cleaning up

Absorb or cover with dry earth, sand or other non-combustible material and transfer to appropriate waste containers. Use clean, non-sparking tools to collect absorbed material. Collect and discard in accordance with local, state and national regulations.

SECTION 7: HANDLING AND STORAGE

Precautions for safe handling

Mildly irritating material. Avoid unnecessary exposure. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. Ground and bond containers when transferring material. Do not get in eyes, on skin and clothing. Wash thoroughly after handling. As with all chemicals, good industrial hygiene practices should be followed when handling this material.

Conditions for safe storage, including any incompatibilities:

Safe storage conditions

Store in a cool dry place. Isolate from incompatible materials. Keep away from heat, sparks, and flame. Keep container closed when not in use.

Materials to Avoid/Chemical Incompatibility

Strong oxidizing agents, Strong acids, Amines

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

OSHA permissible exposure limit (PEL), American Conference of Governmental Industrial Hygienists (ACGIH) Threshold Limit Value (TLV), and any other exposure limit used or recommended by the chemical manufacturer, importer, or employer preparing the safety data sheet, where available:

Chemical Component	OSHA PEL	ACGIH TLV	ACGIH STEL	IDLH
Hydrotreated light distillate (Petroleum)		200 mg/m ³	No data available	No data available

Appropriate engineering controls

Local exhaust ventilation or other engineering controls are normally required when handling or using this product to avoid overexposure.

Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

Engineering controls must be designed to meet the OSHA chemical specific standard in 29 CFR 1910.

Individual protection measures, such as personal protective equipment

Respiratory Protection

Proper ventilation (at a minimum) will be required when handling this product. Use respirators (NIOSH approved) only if ventilation cannot be used to eliminate symptoms or reduce the exposure to below acceptable levels. Follow a respiratory protection program that meets 29 CFR 1910.134 and ANSI Z88.2 requirements whenever work place conditions warrant the use of a respirator.

Thixocal 5000A

Safety Data Sheet

Eye protection	Wear chemical splash goggles when handling this product. Additionally, wear a face shield when the possibility of splashing of liquid exists. Do not wear contact lenses. Have an eye wash station available.
Skin protection	Wear protective gloves. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work.
Gloves	Chemically resistant gloves
Other protective equipment	<p>Wear chemical splash goggles when handling this product. Additionally, wear a face shield when the possibility of splashing of liquid exists. Do not wear contact lenses. Have an eye wash station available.</p> <p>Wear protective gloves. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work.</p>
General hygiene conditions	Use with adequate ventilation Do not use pressure to empty container. Use spark-proof tools and explosion-proof equipment. Keep in air-tight containers- material is hygroscopic. Avoid contact with material, avoid breathing dusts or fumes, use only in a well-ventilated area. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. Ground and bond containers when transferring material. Do not get in eyes, on skin and clothing. Wash thoroughly after handling. As with all chemicals, good industrial hygiene practices should be followed when handling this material.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Physical State	Viscous Liquid
Color	Brown
Odor	Slight Kerosene like
Odor Threshold	No data available
pH	No data available
Melting Point, °C	No data available
Boiling Point, °C	No data available
Initial boiling point and boiling range (°C)	No data available
Flash Point	>= 105 °F(41 °C)
Evaporation Rate	No data available
Flammability (Solid, Gas)	No data available
Lower Flammable/Explosive Limit, % in air	No data available
Upper Flammable/Explosive Limit, % in air	No data available
Vapor Pressure	> 2 mmHg @20°C
Vapor Density	> 1 (Air=1)
Relative Density	> 0.943
Solubility(ies)	Negligible; 0-1%
Partition coefficient: n-octanol/water	No data available
Auto-ignition temperature (°C)	No data available
Decomposition Temperature (°C)	No data available
Viscosity	60000 cP
Volatiles, % by weight	30.8
VOC, Material, lb/gal	2.4
VOC, Material, grams/liter	288
VOC minus exempt solvents & water, g/l	288

Thixocal 5000A

Safety Data Sheet

SECTION 10: STABILITY AND REACTIVITY

Reactivity	Not expected to be reactive.
Chemical stability	Hazardous polymerization will not occur.
Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid (e.g., static discharge, shock, or vibration)	Temperatures above flash point in combination with sparks, open flames, or other sources of ignition. Elevated temperatures. Contamination.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	Under normal conditions of use & storage, decomposition and hazardous decomposition products are unlikely.

SECTION 11: TOXICOLOGICAL INFORMATION

Description of the various toxicological (health) effects and the available data used to identify those effects

Information on the likely routes of exposure (inhalation, ingestion, skin and eye contact)	Eye contact, Skin contact, Inhalation
Symptoms related to the physical, chemical and toxicological characteristics	Causes skin irritation. May cause respiratory irritation. May cause drowsiness or dizziness.

Delayed and immediate effects and also chronic effects from short- and long-term exposure

Ingestion Toxicity	Harmful if swallowed. Estimated to be > 5.0 g/kg; practically non-toxic.
Skin Contact	Can cause minor skin irritation, defatting, and dermatitis.
Inhalation Toxicity	May cause respiratory irritation
Eye Contact	Can cause moderate irritation, tearing and reddening, but not likely to permanently injure eye tissue.
Sensitization	None known.
Mutagenicity	No data available.
Reproductive and Developmental Toxicity	No data available.
Carcinogenicity	There are no carcinogenic ingredients present at or over 0.1%.
STOT-single exposure	Classification has been based on toxicological information of the components in Section 3.
STOT-repeated exposure	Based on available data, the classification criteria are not met.
Aspiration hazard	Based on available data, the classification criteria are not met.

Numerical measures of toxicity (such as acute toxicity estimates)

Chemical Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Hydrotreated light distillate (Petroleum)			Inhalation LC50 (4h) Rat > 20 mg/L

Is the hazardous chemical listed in the National Toxicology Program (NTP) Report on Carcinogens (latest edition) or has it been found to be a potential carcinogen in the International Agency for Research on Cancer (IARC) Monographs (latest edition), or by OSHA?

Thixocal 5000A

Safety Data Sheet

Chemical Name	OSHA Carcinogen	IARC Carcinogen	NTP Carcinogen
No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen.			

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity (aquatic and terrestrial, where available): No data available

Ecological Toxicity Data

Chemical Name	CAS #	Aquatic EC50 Crustacea	Aquatic ERC50 Algae	Aquatic LC50 Fish
No data available				

Persistence and degradability No data available

Bioaccumulative potential No data available

Mobility in soil No data available

Other adverse effects (such as hazardous to the ozone layer) No data available

SECTION 13: DISPOSAL CONSIDERATIONS

Description of waste residues and information on their safe handling and methods of disposal, including the disposal of any contaminated packaging Spent or discarded material may be a hazardous waste. Dispose of by incineration following Federal, State, Local, or Provincial regulations.

Waste codes / waste designations D001

SECTION 14: TRANSPORT INFORMATION

Domestic Ground in containers <=119 GL Corrosion preventive/Non-Regulated

Domestic Ground in containers >119 GL UN1268, PETROLEUM DISTILLATES, N.O.S., (Naphtha Solvent), Combustible liquid, PG III

Shipping name for Export, Air (IATA) UN1268, PETROLEUM DISTILLATES, N.O.S., (Naphtha Solvent),3, PG III

Shipping name for Export, Sea (IMDG) UN1268, PETROLEUM DISTILLATES, N.O.S., (Naphtha Solvent),3, PG III

Marine Pollutant? No

SECTION 15: REGULATORY INFORMATION

Status of formula components on selected national regulatory inventories:

LIST	STATUS
TSCA	All components in this product are on the TSCA Inventory or exempt.
Canadian DSL	All chemical substances in this material are included on or exempted from listing on the Canadian DSL.

Thixocal 5000A

Safety Data Sheet

Chemical Name	CAS #	Regulation	Percent
Naphthalene	91-20-3	Prop. 65 - Cancer	TRACE
Cumene	98-82-8	Prop. 65 - Cancer	TRACE
Benzene	71-43-2	Prop. 65 - Cancer	TRACE
Ethylbenzene	100-41-4	Prop. 65 - Cancer	TRACE
Toluene	108-88-3	Prop. 65 - Developmental and/or Reproductive	TRACE
Benzene	71-43-2	Prop. 65 - Developmental and/or Reproductive	TRACE
Toluene	108-88-3	CERCLA	TRACE RQ=1000 lbs.
Naphthalene	91-20-3	CERCLA	TRACE RQ=100 lbs.
Cumene	98-82-8	CERCLA	TRACE RQ=5000 lbs.
Benzene	71-43-2	CERCLA	TRACE RQ=10 lbs.
Ethylbenzene	100-41-4	CERCLA	TRACE RQ=1000 lbs.
Toluene	108-88-3	SARA 313	TRACE
Cumene	98-82-8	SARA 313	TRACE
Naphthalene	91-20-3	SARA 313	TRACE
Benzene	71-43-2	SARA 313	TRACE
Ethylbenzene	100-41-4	SARA 313	TRACE
No SARA 302 EHS-listed chemicals in this product.		SARA EHS	

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision Date : 01/21/2020

Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

Party Responsible for the Preparation of This Document

Synthetic Oils and Lubricants of Texas
Suite 560
Houston, TX 77068
281-587-0900
www.soltexinc.com

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

Soltex NA GHS SDS