

SULFUR INHIBITOR

- Savings vs. costly retro fill
- Pours directly into oil, no mixing required
- Easily added to transformers in the field
- Restores inhibitor levels to original ASTM specs

Concentrated Antioxidant Metal Passivator & Sulfur Stabilizing Additive

DSI Sulfur Inhibitor is a concentrated blend of advanced antioxidants, metal passivators, and sulfur stabilizers that treats transformer oil with corrosive sulfur problems. In a convenient liquid form, it can be added directly into a de-energized transformer without premixing.

Other treatments for corrosive sulfur only coat or “passivate” copper-containing metals in a transformer, which does nothing to prevent sulfur from attacking other metals, such as iron and aluminum. In addition, different

copper compounds react differently to various passivators. With only one type of copper passivator, you’re only partially protected. DSI Sulfur Inhibitor attacks corrosive sulfur with a powerful blend of metal passivators, sulfur stabilizers, and advanced antioxidants. Copper and other metal ions do not become available for chemical reactions, while sulfur is stabilized to prevent further damage. Oil and paper are protected against further oxidation and chemical reactions. Your transformers are protected with DSI Sulfur Inhibitor.



Applications

- For use with existing contaminated transformer oil
- 55 gallons Inhibit to 2,200 gallons of insulating oil
- Easily used in the field
- Recommended for use in conventional oil and fire-resistant hydrocarbon fluid

Typical Properties

Appearance
Fire Point, D92, °C.
Viscosity, D88, cSt. @ 40 °C.
Density @ 20 °C., g/cc
Pour Point, D97, °C.
Dielectric Breakdown, D1816, kV

Inhibit Fluid

Yellow Liquid
305
10.0
0.87
-24
52



Soltex, Inc.

4 Waterway Sq. Pl. Suite 275
The Woodlands, TX 7738
281-587-0900
orderentry@soltexinc.com
Soltexinc.com

